Ohaus® MB Series

Moisture Analyzers



STANDARD FEATURES

- Fast halogen heating element provides uniform infrared heating and durability for extended use
- Superior weighing performance with readability up to 0.001 g, 0.01% moisture
- Powerful software for simple operation
- Large backlit 128 x 64 pixel Liquid Crystal Display (LCD) for easy viewing
- GLP/GMP compliant format when printed results are required
- Standard RS-232 port for easy communication with printer or computer
- Multi-language display text (English, Spanish, French)

APPROVALS





SPECIFICATIONS

CAPACITY:

MB45: 45 g MB35: 35 g MB25: 110g MB23: 110g

READABILITY:

MB45: 0.01%/0.001g MB35: 0.05%/0.005 q MB25: 0.05%/0.005g MB23: 0.1%/0.01g

REPEATABILITY/STD. DEV:

MB45, 3g sample: 0.05% MB35, 3g sample: 0.18% MB25, 3g sample: 0.2% MB23, 3g sample: 0.3% MB45, 10g sample: 0.015% MB35, 10 g sample: 0.05% MB25, 10 g sample: 0.05% MB23, 10 g sample: 0.1%

TARE RANGE:

Full capacity by subtraction

OPERATING TEMPERATURE:

MB45/35: 50°F to 104°F (10°C to 40°C) MB23/25: 41°F to 104°F (5°C to 40°C)

TEMPERATURE SETTINGS:

MB45: 50-200° x 1°C (increments) MB35: 50-160°C x 5°C (increments) MB23/25: 50 -160 (5 increments)

POWER:

120 VAC, 50/60 Hz

DISPLAY TYPE:

128 x 64 pixel graphical backlit LCD display MB23/25 backlit LCD

PAN SIZE:

3.5 in (90 cm)

OVERALL DIMENSIONS:

MB45/35: 7.5 in W x 6.0 in H x 14.0 in D (190.5 mm W x 152.4 mm H x 355.6 mm D) MB23/25: 6.5 in W x 5 in H x 11 in D (165 mm W x 127 mm H x 279 mm D)

NET WEIGHT:

MB45/35: 10.1 lb (4.6 kg) MB23/25: 5lb (2.3kg)

HEATER TYPE:

Halogen MB23: Infrared (no glass)

TIMER:

MB45: 1 to 120 minutes in 10 second increments MB35: 1 to 120 minutes in 30 second to 60 minute increments, 1 minute increments from 60 to 120 minutes MB23/25: 1 to 99 minutes 30 second increments to 60 minutes

MOISTURE RANGE:

MB45: 0.01% to 100% (0.01% to 1000% for regain mode) MB35: 0.05% to 100%

Commitment Beyond Measurement®

WARRANTY:

Two-year limited warranty

